

GEGRÜNDET 1892

Rektol Klassik, Korbach



Fabrik und Grosshandlung
individueller Oele und Fette

REKTOL SPRAY OIL CLEAR 22

Rektol Spray Oil bright 22 is a preservation oil for storing of tools and machine parts in closed rooms. This product contains also additives for optimal displacement of humidity.

- easy spraying properties with usual spraying equipment
- suitable for apply with a brush
- outstanding oxidation stability, long service life
- counteracts to the oxidation tendency of metals
- good creeping properties

Furthermore this spray oil is also suitable as universal oil for sewing machines, fine mechanics etc.

SPECIFICATIONS

API-SA
VERY BRIGHT COLOUR

TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,86
Flash point	°C	DIN ISO 2592	>200
Pour point	°C	DIN ISO 3016	- 10
Viscosity at 40°C	mm ² /sec	DIN 51562	22,0
Viscosity at 100°C	mm ² /sec	DIN 51562	4,1

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: info@rektol.de · Internet: www.rektol.de